



EZ-100 HB

PARTS A & B

HOW TO USE:

SURFACE PREP: For a proper bond, the surface of concrete must be grinded with low grit metals. If sanding must wear dust mask followed by a vacuuming up dust and solvent wipe.

MIXING: Transfer Epoxy resin into larger mixing container. If adding Metallic pigments, add pigments in to Part A of the epoxy and mix for 3 mins. Let sit several hours to saturate and then remix. Add Epoxy Hardener mix for 3 minutes continually sweeping sides and bottom of container. Mixing Ratio: 2 Part A to 1 Part B.

APPLICATION: Pour mixed material on the countertop. Squeegee at your desired spread rate.

OTHER APPLICATIONS: If casting, pour over entire surface and let it self level.

EXTERIOR APPLICATIONS: Unless installed as a primer Not recommended as epoxies will amber.

DRY-TIME & RECOAT: 14-20 hours tack free, 24-30 hours for foot traffic, 16-24 hours recast, & 4-5 days wheel traffic. Lightly sand the surface and wipe down with denatured alcohol or acetone before applying additional coats or finish coats.

HANDLING, STORAGE, DISPOSAL & CLEAN-UP: May irritate eyes wear gloves as activator is a mild corrosive. Store in clean dry area. Do not freeze. Dispose in accordance with all state local and federal laws. Clean-up tools and equipment with xylene

LIMITATIONS: Do not apply to damp surfaces. Concrete must be ground. Do not add solvent. Do not broadcast as it will effect performance.

POT LIFE:

Mixing 1 full kit, you can expect a pot life of 30 minutes. minutes. Please note that once the epoxy is thoroughly mixed it should be poured out onto the surface being sealed. At that point the surface time is 1 hour, depending on conditions.

PRECAUTIONARY STATEMENT:

PART A: Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment Wear protective gloves / eye protection / face protection

PART B: Do not breathe dust/fume/gas/mist/vapours/spray. Wash with plenty of water. Do no eat, drink or smoke when using this product. Use only outdoors or in a well ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

FIRST AID:

EYES: Flush thoroughly with water, lifting both eyelids. Get Medical Help.

SKIN: Wash with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, Get Medical Help.

INGESTION: Do not induce vomiting. Get Immediate Medical Help.

INHALATION: Remove to fresh air immediately. If breathing difficulty continues, administer oxygen and Get Medical Help.

IN CASE OF FIRE:

This product is not flammable.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

Manufactured In The USA By



**Product warranty for one year from date of manufacture*

For more information on EZChem and all products manufactured by EZChem please visit our website: www.ezchemusa.com