



ACETONE



SOLVENT FOR COATINGS AND SEALERS

*Acetone is a strong, fast-acting solvent that is used as a thinner for acrylic coatings.
Acetone is an effective cleanup solvent.*

PRODUCT HIGHLIGHTS

- **100 % Volatile:** Acetone is completely volatile and leaves no residue.
- **Clear and colorless:** Acetone does not effect the color or clarity of the seal.
- **A range of evaporation rate:** Acetone is fast evaporating and dries very fast at all temperatures.
- **Safety:** Acetone is extremely flammable, and must be used with caution.
- **Available in 1 gallon and 5 gallon.**

PERFECT FOR

- Reducing solids content of sealers for greater penetration
- Cleaning equipment and brushes
- Spraying over an acrylic sealer that shows blushing or uneven surfaces to relax the surface and re-establish a smooth clear surface

QUICK LOOK:

Type: 100% volatile solvent
Toxicity: Harmful if swallowed
Flammability: Flammable, or combustible
Composition: 100% volatile aromatic solvents
Color: Colorless and clear
Odor: Solvent

FOR MORE INFORMATION,
PLEASE SEE SDS.



IMPORTANT: Carefully read all directions, notes and cautions prior to use. Only use this product as directed on the label. Do not spread this product over surface areas greater than 1 sq. foot because fire and health safety risks will increase dramatically. Protect hands with solvent-resistant gloves and eyes with chemical splash goggles. Acetone may soften or damage plastics, synthetics, and many other finishes. Do not use to clean or flush spray equipment.

Manufactured In The USA By



*Product warranty for one year from date of manufacture
For more information on EZChem USA and all products manufactured by EZChem please visit our website: www.ezchemusa.com



ACETONE

HOW TO USE:

Acetone should be used with good ventilation. **To dilute a sealer:** add up to one pint per gallon of sealer and mix well. **To clean tools or brushes:** soak until the sealer is completely dissolved and rinse with clean solvent. **For surface restoration:** spray Acetone over the surface to wet thoroughly, and let dry completely before allowing traffic on the floor.

PRECAUTIONARY STATEMENT:

Extremely flammable. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from work site. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and wait until vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. Close container after use. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, do not use this product. A dust mask does not provide protection against vapors.

FIRST AID:

IF INGESTED: Do not induce vomiting. Get Immediate Medical Help.
IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. Get Medical Help.
IF ON SKIN: Rinse off thoroughly with soap and water. Wash contaminated clothing before reuse.
INHALATION: Remove to fresh air. Give resuscitation and oxygen if required. Get Medical Attention.

IN CASE OF FIRE:

Preferably use an alcohol resistant foam or water spray, polyvalent foam, BC powder or carbon dioxide. Solid water jet ineffective as extinguishing medium.

STORAGE:

Do not use or store this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc. Keep it in a cool, dry place, out of direct sunlight, at temperatures below 120°. Keep container closed when not in use. Do not reuse this container.

DISPOSAL:

If container is corroded, rusted or shows signs of deterioration, dispose of product. Dispose of empty cans and leftover product at your local household hazardous waste collection facility. If one is not available, dispose of in accordance with federal, state and local regulations.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP

24 Hours a Day contact:
INFOTRAC at 1-800-535-5053