



BOND COAT

THIN CEMENTICIOUS OVERLAY



BOND COAT IS A THIN CEMENTICIOUS OVERLAY APPLIED AS A BASE COAT FOR SPRAY DECK, STAMP MIX, TROWEL DOWN, VERTICAL STAMP MIX OR OTHER SIMILAR FINISHES.

PRODUCT HIGHLIGHTS

- High bond strength.
- Improved resistance to weather and freeze thaw cycles.
- Can be integrally colored with EZChem EZ Color Paks
- Can be colored/stained topically with EZChem Enviro Stains or Earthtone Concrete Stains.
- Packaged in 50lb bags
- Available in white or grey.

USES

- Primarily used for creating base/skim coats.
- Bond coat provides a permanent bond when applied to properly prepared and cleaned concrete surfaces. It is typically used as a base (bond coat) for other overlay mixes (stamp mix, texture blend, spray mix or other similar finishes).
- Bond coat should still be wet when the overlay mix (typically stamp mix) is applied over it.

QUICK LOOK:

Type : Single component bonding coat mix

Toxicity: Non-toxic

VOC's: Zero

Flammability: Non-flammable

Composition: Cementitious carrier and Polymeric bonding agent

Odor: Very mild

Coverage: 175-200 Sq. Ft. @ 1/16" per 50lb bag

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.





BOND COAT

SURFACE PREPERATION:

Strip any sealer off the floor with Citra Peel or Hot Strip. You may also grind or shot blast the floor. Any surface oils should be removed with Citra Pro degreaser and then use Super Blue to boil out the pores.

HOW TO USE:

Bond coat is applied to the prepared concrete surface prior to applying the overlay mix.

Add 50 lb bag of bond coat 1K powder to approximately 5 quarts (minimum 4 maximum 7) of water.

Mix in a clean 5 gallon pail with a ½" mixer drill (Do not use a cement mixer)

Add EZChem EZ Color Pak (blend the Color Pak into the water first) if integral color is desired.

Add half the powdered material to the water, mix untill lump free, let sit for 5 minutes, then blend in the other half.

Apply with a magic trowel (squeegee), steel trowel, brush, broom or roller

Bond coat is applied to a maximum thickness of 1/8".

PRECAUTIONARY STATEMENT:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do no eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

FIRST AID:

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconcious person.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053