



BROOM FINISH MIX



SINGLE COMPONENT CEMENTICIOUS OVERLAY

BROOM FINISH MIX IS A SINGLE COMPONENT OVERLAY SYSTEM THAT BONDS TO ALL CLEAN CONCRETE SURFACES TO PRODUCE A ROCK HARD WEATHER PROOF SURFACE. IT CAN BE TROWELED OR SQUEEGEE APPLIED AS A THIN BOND COAT OR APPLIED BY HOPPER SPRAY GUN FOR A TEXTURED SURFACE.

PRODUCT HIGHLIGHTS

- High bond, flexural and compressive strength. Consistent and evenly textured finish.
- Can be integrally colored with EZChem EZ Color Paks.
- Can be stained with EZChem Enviro Stain or Earthtone Stain for a wide array of decorative finishes.
- Can be sealed with EZChem Clear Acrylic Sealer or Colored Acrylic Sealer for a consistently colored and durable surface.
- Packaged in 50lb bags
- Available in white and grey.

USES

- Can be used over interior or exterior, horizontal and vertical concrete surfaces that are structurally sound and properly prepared.
- Broom Finish Mix is typically used for the finishing of concrete walls, stairs, pool decks, patios and walkways. It is easy to work with and enables the installation of a consistent and evenly textured finish.
- When applied with a compressor driven Hopper Gun the application is fast and easy, and the texture consistent.
- Broom Finish Mix sets to a rock hard surface that resists water penetration and provides a durable and beautiful textured surface.

QUICK LOOK:

Type :
Toxicity:
VOC's: Zero
Flammability: Non-flammable Composition:
Odor: N/A
Coverage: Base coat = approx 100-120 sq.ft Sq ft
Finish coat = approx 150-60 sq.ft
depending on texture)

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

Application Temperature: 50°-100°F
Cured: 28 days

FOR MORE INFORMATION,
PLEASE SEE SDS.





BROOM FINISH MIX

SURFACE PREPERATION:

Just prior to applying Broomfinish Mix the substrate must be primed with Bond It primer. Do not allow Bond It primer to dry completely. Broomfinish Mix must be applied over wet Bond It.

HOW TO USE:

Broomfinish Mix is typically applied to a damp surface. Remove any puddles and standing water (Saturated surface dry) prior to installation.

Add 50 lb bag of Broomfinish Mix to approximately 5.5 quarts (minimum 4.5 maximum 6.5) of water.

Mix in a clean 5 gallon pail with a ½" mixer drill (Do not use a cement mixer)

Add EZChem EZ COLOR PAK (blend the Color Pak into the water first) if integral color is desired.

Add half the powdered material to the water, mix untill lump free, let sit for 5 minutes, then blend in the other half.

Apply with a hopper gun, magic trowel (squeegee), steel pool trowel, brush, broom or roller

For a knockdown texture use 8-15 PSI through a relatively large orifice. As the wet, glossy material begins to dry to a matte or dull finish, it should be knocked down with a pool trowel or metal squeegee

For a bubble texture use 40 Psi through a relatively small orifice.

PRECAUTIONARY STATEMENT:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do no eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

FIRST AID:

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconcious person.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053