



# CLEAR COAT VOC GLOSS FINISH

## **HOW TO USE:**

Always insure good ventilation when using Clear Coat VOC.

1. Concrete surface must be clean, dry and free of all contaminants and water. EZ Chem recommends using Super Blue for surface cleaning and preparation.
2. Surface and air temperature must be no less than 40°F and no more than 80°F. EZ Chem recommends applying on cool, overcast days or in the morning.
3. Clear Coat VOC may be applied by brush, roller(3/8in - 1/2in nap), or solvent resistant pump up sprayer. Apply a thin uniform coat at the rate of one gallon to 250-350 Sq. Ft. (40 m<sup>2</sup>)
4. Allow coating to dry for 4-6 hours and apply a second coating for maximum durability. Allow at least 24 hours to dry before foot traffic.
5. Equipment may be cleaned with xylene or lacquer solvent. Dispose of contents/container according to local, state and federal regulations.

## **PRECAUTIONARY STATEMENT:**

Extremely flammable. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from work site. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and wait until vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. Close container after use. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, do not use this product. A dust mask does not provide protection against vapors. Wear protective gloves/glasses/respirator when using this product.

## **FIRST AID:**

INHALATION: Remove to fresh air immediately. If breathing is difficult, administer oxygen. Get Medical Help.

INGESTION: Do not induce vomiting. Get Immediate Medical Help.

EYES: Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

SKIN: Wash with soap and water. Remove and launder contaminated clothing before reuse.

## **IN CASE OF FIRE:**

Use foam, dry chemical, sand, earth, CO<sub>2</sub> to extinguish. Over heated or burning product will boil off flammable fumes and heavy smoke.

## **FOR PROFESSIONAL USE ONLY**

### **FOR EMERGENCY HELP**

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

Manufactured In The USA By



*\*Product warranty for one year from date of manufacture*

For more information on EZChem USA and all products manufactured by EZChem please visit our website: [www.ezchemusa.com](http://www.ezchemusa.com)