



CLEAR COAT VOC GLOSS FINISH

25% CLEAR ACRYLIC SEALER



CLEAR COAT VOC IS A SOLVENT BASED, PURE ACRYLIC COATING THAT FORMS A TOUGH CRYSTAL CLEAR COATING THAT SEALS, BEAUTIFIES, AND PROTECTS ALL CONCRETE SURFACES. IT IS COLORLESS, AND NEVER YELLOW.

PRODUCT HIGHLIGHTS

- **Clear and Colorless:** Clear Coat VOC goes on water white and never yellows.
- **Environmental:** Clear Coat VOC contains no chlorinated solvents or other ozone depleting solvents, and it is VOC compliant in NJ, NY and other Northeast US states.
- **Seals and Beautifies:** Clear Coat VOC penetrates into the pores of the concrete and seals out dirt and stains as it seals in the beauty.
- **Dries to a smooth, tough, glossy finish:** Clear Coat VOC flows and levels to prevent brush strokes or roller marks, and dries smooth and glossy.
- **Dries quickly:** The active solvent system in Clear Coat VOC evaporates quickly and completely leaving only the acrylic polymer. Once dry, all flammable solvent is gone and the area is safe and ready to use.
- **Accepts water based polish:** For use indoors, the finished coating can be over coated with a water based polish, such as EZ-Glo, to act as a renewable wear surface.
- **Available in 1 gallon and 5 gallon.**

PERFECT FOR

- Sidewalks
- Patios
- Driveways

Clear Coat VOC is applied by brush, roller or sprayer onto cured, dry and clean concrete. Applied over concrete stains, Clear Coat VOC seals, enhances, and locks in the color to produce a permanent and beautiful stained floor. Once dry, a second coat may be applied to enhance the floor.

QUICK LOOK:

Type: VOC compliant solvent based pure acrylic coating
Toxicity: Harmful if swallowed. Avoid breathing vapors.
VOC's: Less than 400
Flammability: Flammable
Composition: Pure high molecular weight acrylic polymers in VOC compliant solvent base.
Color: Colorless and clear
Odor: Solvent
Coverage: 250-350 sq.ft.
**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.



Note: Low VOC solvent based sealers dry faster than traditional solvent based sealers.

Manufactured In The USA By



**Product warranty for one year from date of manufacture*

For more information on EZChem USA and all products manufactured by EZChem please visit our website: www.ezchemusa.com



CLEAR COAT VOC

GLOSS FINISH

HOW TO USE:

Always insure good ventilation when using Clear Coat VOC.

1. Concrete surface must be clean, dry and free of all contaminants and water. EZ Chem recommends using Super Blue for surface cleaning and preparation.
2. Surface and air temperature must be no less than 40°F and no more than 80°F. EZ Chem recommends applying on cool, overcast days or in the morning.
3. Clear Coat VOC may be applied by brush, roller(3/8in - 1/2in nap), or solvent resistant pump up sprayer. Apply a thin uniform coat at the rate of one gallon to 250-350 Sq. Ft. (40 m2)
4. Allow coating to dry for 4-6 hours and apply a second coating for maximum durability. Allow at least 24 hours to dry before foot traffic.
5. Equipment may be cleaned with xylene or lacquer solvent. Dispose of contents/container according to local, state and federal regulations.

PRECAUTIONARY STATEMENT:

Extremely flammable. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from work site. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and wait until vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. Close container after use. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, do not use this product. A dust mask does not provide protection against vapors. Wear protective gloves/glasses/respirator when using this product.

FIRST AID:

INHALATION: Remove to fresh air immediately. If breathing is difficult, administer oxygen. Get Medical Help.

INGESTION: Do not induce vomiting. Get Immediate Medical Help.

EYES: Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

SKIN: Wash with soap and water. Remove and launder contaminated clothing before reuse.

IN CASE OF FIRE:

Use foam, dry chemical, sand, earth, CO2 to extinguish. Over heated or burning product will boil off flammable fumes and heavy smoke.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

Manufactured In The USA By



**Product warranty for one year from date of manufacture*

For more information on EZChem USA and all products manufactured by EZChem please visit our website: www.ezchemusa.com