



ENVIRO WB SEALER

HOW TO USE:

After Enviro Stain application has been rinsed and thoroughly dry, usually 24 hours, apply Enviro WB Sealer in two thin uniform coats using a roller.

Allow the coating to dry for one hour before applying the second coat.

In heavy traffic areas, a third coat can be applied as above, or apply two coats of EZ-Glo polish as a renewable wear surface. Allow 24 hours drying before walking on floor.

Note: A small test area is recommended. Enviro WB Sealer can be used over other colorants for protection but will not "pop" color on Acid Stained floors.

PRECAUTIONARY STATEMENT:

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Dispose of contents/container according to local, state and federal regulations.

FIRST AID:

EYES: Flush with quantities of water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

IF SWALLOWED: Drink two glasses of water. Get Immediate Medical Help.

SKIN: Wash with soap and water.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053