



HOT STRIP

COATING REMOVER AND STRIPPER



HOT STRIP IS A POWERFUL INDUSTRIAL STRENGTH EMULSIFYING SOLVENT STRIPPER FOR ALL ACRYLIC SEALERS AND OTHER COATINGS. HOT STRIP WILL ALSO DISSOLVE AND EMULSIFY HEAVY GREASE AND GREASY SOIL DEPOSITS. IT IS SAFE TO USE ON ALL CONCRETE, STONE, WOOD OR METAL SURFACES.

PRODUCT HIGHLIGHTS

- **Emulsifying action:** Hot Strip not only dissolves tough to remove coatings, but the emulsifying action breaks down the dissolved coating so that scrubbing with water removes all of the old coating down to bare concrete. Nothing is left behind.
- **Fast action:** Hot Strip will penetrate and soften the old coating in 20 to 30 minutes so that it can be scrubbed up and emulsified with water and flushed off.
- **No neutralizing necessary:** Hot Strip contains no acids or harmful reactive components. Just scrub up the dissolved coating, rinse it off, and let the floor dry. SuperBlue™ may be applied immediately if there are stains to be removed or to profile.
- **Economical:** The fast acting Hot Strip formula means less labor and less time wasted. This saves money. Stable in storage: Stored in its original container, Hot Strip remains stable for long periods of time.
- **Available in 1 gallon and 5 gallon.**

USES

Hot Strip is used to strip off old or heavy sealer coatings where ground in soil makes the area look dingy. It can also be used to remove most sealers where a color change is desired. In conjunction with Super Blue it is ideal in renovating and redoing a concrete floor.

QUICK LOOK:

Type: Heavy duty solvent type coating remover
Toxicity: Harmful if swallowed, use with good ventilation
VOC's:
Flammability: Extremely Flammable
Composition: Biodegradable surfactants, and non-chlorinated solvents.
Color: Straw
Odor: Solvent
Coverage:
**Coverage rates may vary depending on porosity, dilution, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.





HOT STRIP

HOW TO USE:

1. To remove sealers and concrete coatings, apply a liberal coat of Hot Strip and let it penetrate for 5 to 20 minutes, depending on the thickness of the coating.
2. Apply a small amount of water and agitate thoroughly with a scrubber or stiff broom.
3. Scrape off the emulsified coating. Dispose of according to local, state and federal regulations.
4. Rinse the area and mop or vacuum up water.

STORAGE AND DISPOSAL:

Store product in the original container, tightly closed. Store at room temperature. Do not store near heat sources or open flames or sparks. Do not transfer to other containers for storage. Rinse empty container with water and discard. Empty container may contain flammable fumes. Do not puncture, cut or weld as an explosive reaction can occur. Dispose of contents/container according to local, state and federal regulations.

PRECAUTIONARY STATEMENT:

Extremely flammable. Vapors may cause flash fire or ignite explosively. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/ face protection/respirators. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. Close container after use. Do not use in areas where vapors can accumulate and concentrate. **DO NOT USE INDOORS.** A dust mask does not provide protection against vapors. This product is toxic to fish and marine life. Do not use, spill, or store in a way that will allow product or rinsate to enter streams, lakes or water ways where fish or marine life may be adversely affected. Use caution around plants and grass areas as this product could harm them.

FIRST AID:

IF SWALLOWED: Do not induce vomiting. Rinse mouth with water and Get Immediate Medical Attention. Never give anything by mouth to an unconscious person.

IF IN EYES: Flush with quantities of water for 15 minutes, lifting both eyelids. Get Medical Help.

INHALATION: Remove to fresh air immediately. Give oxygen if breathing is difficult. If difficulty persists, Get Medical Help.

ON SKIN: Wash off with water then soap and water. Remove contaminated clothing and launder before reuse. If irritation develops, Get Medical Help.

IN CASE OF FIRE:

Use foam, water spray or fog, dry chemical, sand, earth, or CO2 to extinguish. Do not use water jet.

FOR INDUSTRIAL USE ONLY

FOR OUTDOOR USE ONLY

Because of strong solvent smell, this product should only be used outside in well ventilated areas.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

