



# HYDRATIQUE

## ANTIQUE COLOR WASH



**HYDRATIQUE IS A VERSATILE COLORING AGENT THAT CAN BE EASILY APPLIED AND WILL HOLD FAST TO ANY TEXTURED CONCRETE SURFACE. SOLD AS A POWDER, APPLIED AS A LIQUID WASH COAT, HYDRATIQUE CAN BE USED TO REVITALIZE A WEATHERED CONCRETE SURFACE OR ADD AN ANTIQUE COLOR TO A FRESHLY TEXTURED SURFACE. THIS PRODUCT IS WATER-BASED, NON-HAZARDOUS, AND ZERO V.O.C.**

### PRODUCT HIGHLIGHTS

- No power washing
- Very economical to use to restore color on weathered concrete
- Less mess, less clean-up time
- More control of the antiquing process
- Can be used in place of traditional antique release
- Use multiple colors for more natural look
- One 3 pound pail of Hydratique covers approximately 2,000-4,000 square feet.

### USES

Hydratique is ideal for concrete surfaces where an antique effect is desired.

Hydratique can revitalize a weathered concrete surface.

### QUICK LOOK:

Type : Powder  
Non hazardous  
VOC's: Zero  
Flammability: Non-flammable  
Composition: portland cement, cement and additives

Coverage: 2,000 - 4,000 sq.ft.

*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.





# HYDRATIQUE

## HOW TO USE:

Open the bag of Hydratique powder. It will contain a plastic scoop. In a separate pail, mix add 1 gallon of water. Mix in 1.5 scoops (6 oz) of the powder. Use more or less of the product in one gallon of water to achieve different results in color intensity. Hydratique can be mixed readily with a stir stick. There is no need to mechanically mix. The product in the container will need to be agitated periodically during application to keep the solids from settling. This settling property of Hydratique is important in reaching the desired antique effect. Before applying product to unsealed concrete, Mist the surface with water so the liquid color will have time to even out and settle properly.

The most basic technique to apply Hydratique is to simply pour the liquid color straight onto the horizontal concrete surface with a pitcher or watering can, making sure to leave a uniform coat of liquid over the area to be covered. If necessary, liquid Hydratique can be spread quickly and easily with a clean push broom. Be sure to have clean water handy to spray on the surface to make sure the color spreads uniformly. Hydratique can be cleaned up readily with water while it is still wet and can be wiped off with a clean dry sponge when dry.

## PRECAUTIONARY STATEMENT:

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation, wear respiratory protection. Dispose of contents/container to an approved waste disposal plant. Product contains Portland Cement which when wet can irritate the skin and seriously damage the eyes. Product may contain titanium dioxide, which is considered to be a class 2B carcinogen.

## FIRST AID:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Move person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

This product is not flammable.

## IN CASE OF FIRE:

## FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

