



# SUPER DECORATIVE SEALER HIGH SHEEN

## SILOXANE MODIFIED METHYL METHACRYLATE

*SUPER DECORATIVE SEALER is a non-yellowing, high gloss, siloxane modified methyl methacrylate with excellent adhesion to properly prepared concrete substrates. Superior resistance compared to standard sealers used to protect exterior concrete.*

### PRODUCT HIGHLIGHTS

- Minimizes damage due to water and salt water from de-icing road salts.
- Excellent penetration and adhesion to clean, unsealed new or old concrete
- Non-yellowing
- Can be applied as a reseat on certain solvent based acrylic sealers
- VOC compliant for most areas in the United States and Canada

### USES

- Concrete Pool Decks
- Stamped & Stenciled Concrete
- Acid Stained Concrete
- Overlaid / Microtopped Concrete
- Exposed Aggregate Concrete
- Smooth Trowel Concrete
- Broom Finish Concrete

### QUICK LOOK:

Solids / Active Content, % by weight: 25% +/- 1%  
Dry Time / Tack Free: 30 minutes - 1 hour  
Dry Time / Foot Traffic: 4-6 hours  
Dry Time / Heavy Traffic: 24-48 hours  
Re-Coat Time Window: 4-24 hours  
Application Temperature: 50° F - 80° F  
VOC's: Less than 350 grams/Liter  
Appearance - Wet: Clear  
Appearance - Dry: Clear and High Gloss

FOR MORE INFORMATION,  
PLEASE SEE SDS.





# SUPER DECORATIVE SEALER HIGH SHEEN

## HOW TO USE:

Always insure good ventilation when using Super Decorative Sealer. When using indoors, HVAC ducts, etc. should be covered to prevent fumes from discharging.

**SURFACE PREP:** Concrete must be clean and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, the sealer may have white spots and have premature delamination and failure.

Substrate and air temperature must be no less than 40° F and not exceed 80° F. If applied outside these limits the sealer may achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing. Note that direct sunlight, substrate temperature can exceed 150° F which can cause extreme bubbling issues. Low VOC solvent based sealers dry faster than traditional 700 VOC sealers. Apply on cool, overcast days to avoid issues. Do not apply if the temperature is expected to achieve 85° F or higher.

**MIXING:** Stir well before using. Material may separate during long term storage.

**COVERAGE RATE:** *First Coat: 200-300 sq. ft./gallon. Optional Second Coat: 300-400 sq. ft./gallon.* Coverage rates may vary depending upon surface porosity. Excessive build up should be avoided.

**APPLICATION:** Apply using a 3/8" long nap roller cover using long uniform strokes at approximately 200-400 sq. ft./gal. depending on porosity and texture of substrate. An airless sprayer containing a .519 tip size may be used as well. Thick or puddle areas may prevent the solvent from evaporating and may be susceptible to moisture intrusion which may cause white spots. Applying to thin may cause sealer to prematurely de-laminate, flake or wear away. Allow sealer to dry for 24 hours for light traffic and at least 48 hours for heavy traffic. If applying 2 coats, wait approximately 4-6 hours between coats. **FOR PERSONAL PROTECTION USE GLOVES, GOGGLES, AND RESPIRATORS. DO NOT THIN!**

When using as a cure & seal, apply only one coat to meet specifications. Extreme bubbling and/or hazing may occur due to lack of permeability.

*\*It is always recommended to test the product in a small, inconspicuous area on the concrete you are planning to apply to, to ensure desired results. Coverage rates may vary depending on porosity, density and texture. Do not exceed 400 sq. ft./gal. Applying to thin of a coating may cause inadequate film formation. DO NOT USE ON BRICK.*

## PRECAUTIONARY STATEMENT:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep away from any possible contact with water, because of violent reaction and possible flash fire. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wash hands thoroughly after handling. Wear protective clothing, gloves, safety glasses, and use a respirator. Do not eat, drink or smoke when using this product. Store in a well-ventilated place. Make sure all HVAC vents are covered prior to use to prevent fumes from traveling. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, do not use this product. Keep container tightly closed. Dispose of contents/ container according to local, state and federal regulations.

## FIRST AID:

**INHALATION:** Remove to fresh air immediately. If breathing is difficult, administer oxygen. Get Medical Help. **INGESTION:** Do not induce vomiting. Get Immediate Medical Help.

**EYES:** Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

**SKIN:** Wash with soap and water. Remove and launder contaminated clothing before reuse.

## IN CASE OF FIRE:

Use foam, dry chemical, sand, earth, or CO2 to extinguish. Over heated or burning product will boil off flammable fumes and heavy smoke.

## FOR PROFESSIONAL USE ONLY

### FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

Manufactured In The USA By



*\*Product warranty for one year from date of manufacture*

For more information on EZChem USA and all products manufactured by EZChem please visit our website: [www.ezchemusa.com](http://www.ezchemusa.com)