

# WATER BASED EPOXY PARTS A & B

### HIGH GLOSS SURFACE SEALER



WATER BASED EPOXY IS A SUPER HIGH GLOSS EPOXY SURFACE SEALER FOR ALL INTERIOR LATERAL CONCRETE SURFACES, OVERLAYS, METALLICS, COUNTER TOPS, CONCRETE FLOORS & CHIP BROADCAST SYSTEMS. LOW VOC.

#### **PRODUCT HIGHLIGHTS**

- High gloss clear finish, with a clear wet appearance.
- Low Odor
- Resistant: Common chemicals, solvent resistant
- Excellent abrasion resistance
- VOC Compliant
- Available in 1.25gallon, 2.5gallon and 5gallon kits
- Mixing Ratio: 4:1 (4 Parts A to 1 Part B)

#### QUICK LOOK: PART A

Solids Content: 60%

Toxicity: Harmful if swallowed

VOC's: Low

Flammability: Non-Flammable

Composition: Color:

Coverage: 400-500sq.ft. per gallon @ 3-4mLs

\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.

silibala be avolaca.

FOR MORE INFORMATION, PLEASE SEE SDS.



Ratio: 4:1 by volume

#### **USES**

Effective on many interior applications where a low odor, abrasion resistant coating is required.

#### **SPECS**

- 400-500 sq. ft. per gallon
- 2-3 Mils Wet
- Pot Life = 1.5 hrs +
- Tack Free for 2 3 hours
- Re Coat = 4 20 hours
- Foot Traffic = 24 hours
- Vehicle Traffic = 72 hours

#### **QUICK LOOK: PART B**

Solids Content: 60%

Toxicity: Harmful if swallowed

VOC's: Low

Flammability: Non-Flammable

Composition:

Color: Odor:

Coverage: 400-500sq.ft. per gallon @ 3-4mLs

\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.

FOR MORE INFORMATION, PLEASE SEE SDS.





Ratio: 4:1 by volume





## WATER BASED EPOXY PARTS A & B

#### **HOW TO USE:**

Add four parts by volume of Part A to one part of Part B and blend thoroughly until completely mixed. May be used immediately. Apply by brush, roller or spray. Dry to touch in 2-3 hours. A second coat can be applied in 3-4 hours. Use detergent and water for clean up.

#### **POT LIFE:**

The pot life of this product is one hour. Shelf Life is up to one year from manufacture date in its original, unopened container stored at room temperature.

#### **PRECAUTIONARY STATEMENT:**

**PART A:** Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Dispose of contents/ container according to local, state and federal regulations.

**PART B:** Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Dispose of contents/ container according to local, state and federal regulations.

#### **FIRST AID:**

EYES: Flush thoroughly with water, lifting both eyelids. Get Medical Help.

SKIN: Wash with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, Get Medical Help.

INGESTION: Do not induce vomiting. Get Immediate Medical Help.

INHALATION: Remove to fresh air immediately. If breathing difficulty continues, administer oxygen and Get Medical Help.

#### **IN CASE OF FIRE:**

This product is not flammable.

#### FOR PROFESSIONAL USE ONLY

#### **FOR EMERGENCY HELP**

24 Hours a Day contact: INFOTRAC at 1-800-535-5053

