



# WHITE OUT

## "BLUSH" REMOVER FOR SOLVENT BASED SEALERS



**WHITE OUT IS A UNIQUE BLEND OF SOLVENTS AND RETARDERS FOR REMOVING BLUSHING CAUSED BY MOISTURE TRAPPED UNDER SOLVENT BASED SEALERS.**

### PRODUCT HIGHLIGHTS

- Available in 1 gallon and 5 gallon.

### USES

White Out is used to remove "blushing" in solvent-based sealers that have been applied over concrete with excess moisture content. White Out dissolves acrylic sealers and allows trapped moisture to dissipate enabling the sealer to penetrate into the concrete substrate. Once the White Out has dried, the surface is ready to re-seal

### QUICK LOOK:

**Type:**

**Toxicity:** May be harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

**VOC's:**

**Flammability:** Flammable

**Composition:**

**Color:** Colorless

**Odor:** Solvent

**Coverage:** 320 SqFt. per 3.78 L. (1 Gal.)  
1600 SqFt. per 18.9 L. (5 Gal.)

*\*Coverage rates may vary depending on porosity, dilution, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.





# WHITE OUT

## **LIMITATIONS:**

Do not apply when temperature is above 38°C (100°F) and below 4°C (40°F) During installation below 13°C (55°F) drying time increases. Use on solvent based acrylic sealers only. Do not use on plastics or siding.

## **INSTALLATION DATA:**

Cover the affected area by spraying or pouring and scrub in with solvent compatible brush. Repeat if necessary until blush has disappeared. Apply new coat of sealer to area.

## **STORAGE AND HANDLING:**

Store in cool dry area away from open flame and spark. Caution flammable Contact may cause severe burns. Avoid breathing vapors. Avoid eye contact. Wear protective clothing, vapor mask & eye protection. Use only in well ventilated areas. If swallowed call physician immediately. Contains Xylene. Keep away from children. Extinguishing Media: Foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Special Firefighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus. Unusual Fire & Explosion Hazards: Closed containers may rupture when exposed to extreme heat. Vapors may form an explosive mixture in the air. See SDS for additional information.

## **PRECAUTIONARY STATEMENT:**

Highly flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation. Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapors, spray. Wash exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, face protection, protective clothing, protective gloves. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to comply with local, state and federal regulations. Keep cool.

## **FIRST AID:**

IF INGESTED: Do not induce vomiting. Get Immediate Medical Help.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. Get Medical Help.

IF ON SKIN: Rinse off thoroughly with soap and water. Wash contaminated clothing before reuse.

INHALATION: Remove to fresh air. Give resuscitation and oxygen if required. Get Medical Attention.

## **IN CASE OF FIRE:**

Use foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.

## **FOR EMERGENCY HELP**

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053