

XYLENE

SOLVENT FOR COATINGS AND SEALERS



XYLENE IS FOR USE AS A DILUENT FOR ACRYLIC COATINGS AND AS A GENERAL PURPOSE SOLVENT.

PRODUCT HIGHLIGHTS

- **100 % volatile:** Xylene is completely volatile and leave no residue.
- **Clear and colorless:** Xylene does not effect the color or clarity of the seal.
- **A range of evaporation rate:** Xylene is fast evaporating and dries very fast at all temperatures.
- **Safety:** Xylene is extremely flammable, and must be used with caution.
- **Available in 1 gallon and 5 gallon.**

USES

Use Xylene to reduce solids content of sealers for greater penetration or to clean equipment and brushes as well as spraying over an acrylic sealer that shows blushing or uneven surfaces to relax the surface and re-establish a smooth clear surface.

QUICK LOOK:

Type: 100% volatile solvent

Toxicity: Harmful if swallowed

VOC's:

Flammability: Flammable

Composition: 100% volatile aromatic solvents

Color: Colorless

Odor: Solvent

Coverage:

**Coverage rates may vary depending on porosity, dilution, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.





XYLENE

HOW TO USE:

To dilute a sealer, add up to one pint of solvent per gallon of sealer and mix well.

PRECAUTIONARY STATEMENT:

Extremely flammable. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from work site. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and wait until vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. Close container after use. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, do not use this product. A dust mask does not provide protection against vapors.

FIRST AID:

IF INGESTED: Do not induce vomiting. Get Immediate Medical Help.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. Get Medical Help.

IF ON SKIN: Rinse off thoroughly with soap and water. Wash contaminated clothing before reuse.

INHALATION: Remove to fresh air. Give resuscitation and oxygen if required. Get Medical Attention.

IN CASE OF FIRE:

Use foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053