



# CURE AND SEAL

## **HOW TO USE:**

The preferred method of application is to use a solvent resistant pump up sprayer, and spray a thin uniform coat of Cure and Seal over the entire surface of the concrete as soon as it is finished and all surface water is absorbed. Do not spray over puddles of water. When the forms are removed, spray the exposed sides of the concrete. Alternatively, Cure and Seal may be brushed or rolled on the surface. Use only when temperatures are between 40-90F to keep sealer from bubbling, blushing or hazing. When applying sealer, wait approximately 4-6 hours between coats. Allow sealer to dry at least 24 hours for light traffic and 48 hours for heavy traffic.

## **PRECAUTIONARY STATEMENT:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep away from any possible contact with water, because of violent reaction and possible flash fire. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Make sure all HVAC ventilation ducts are covered before use to insure solvent fumes are not distributed. Use in well ventilated areas. Wash hands thoroughly after handling. Use gloves, goggles and respirators for protection. Do not eat, drink or smoke when using this product. Store in a well ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local, state and federal regulations.

## **FIRST AID:**

INHALATION: Remove to fresh air immediately. If breathing is difficult, administer oxygen. Get Medical Help.

INGESTION: Do not induce vomiting. Get Immediate Medical Help.

EYES: Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

SKIN: Wash with soap and water.

## **IN CASE OF FIRE:**

Use foam, dry chemical, CO2, sand or earth to extinguish.

## **FOR PROFESSIONAL USE ONLY**

### **FOR EMERGENCY HELP**

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

