

May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

EZ-100 (MVB) FAST CURE - EPOXY - PART B

SECTION I: IDENTIFICATION

EZCHEM, Inc. 92 Don Westbrook Ave. N.

lasper, GA 30143

Product Name: EZ-100 - MVB FC - Part B

Product Use: Epoxy Curing Agent

Emergency Telephone Number: I-800-535-5053 Telephone Number for Information: 706-253-5055

SECTION II: HAZARD IDENTIFICATION

Signal Word: DANGER

Hazard Classification:

Acute Toxicty, Oral, Catagory 4

Serious Eye Damage, Category I

Skin Corrosion, Catagory IB

Skin Sensitization, Catagory I

Repr.2 Suspected of damaging fertility or the unborn child

Causes damage to organs through prolonged or repeated exposure

Hazard Statements:

H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H361- Suspected of damaging fertility or the unborn child

H372- Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements:

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P352 – Wash with plenty of water/...

P270 – Do no eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well ventilated area.

P272 – Contaminated work clothing should not be allowed out of the workplace.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P312 - Call a POISON CENTER/doctor/...if you feel unwell.

P301 +P330 + P331 – IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 – IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing Rinse skin with water/shower.

P304 + P340 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfor table for breathing.

P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 – If skin irritation or rash occurs: Get medical advice/attention.

P308+P311- If exposed or concerned: Call a POISON CENTER/doctor/...

P322 Specific measure (see...on this label)

P363 – Wash contaminated clothing before reuse.

P403+P233 - Store in well ventilate place. Keep container tightly closed.

P405 – Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant.





May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

Chemical Name:	CAS No.	Percentage %
Phenol, styrenated	61788- 44 -1	25-50%
Polyoxpropylenediamine	9046-10-0	25-50%
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	25-50%
2-piperazin- I ylethylamine	140-31-8	2.5-10%
2,4,6-tris (dimethylaminomethyl)phenol	90-72-2	2.5-10%

SECTION IV - FIRST AID MEASURES

EYES: Flush eyes immediately with plenty water thoroughly for at least 15 minutes, lifting both eyelids. Get Medical HELP.

SKIN: Immediately flush with water for at least 15 minuteS. Remove contaminated clothing and footwear while flushing skin with water. Launder clothing and dispose of footwear. Seek medical attention.

INGESTION: Do Not Induce Vomiting. Rinse mouth with water. Call a physician or poison control center immediately.

INHALATION: Get immediated medical attention. Take precautions to ensure your own safety. Remove fom area of exposure. If unconcious, give oxygen. Give artificial respiration if not breathing. Avoid mouth to mouth contact by using a barrier device. If the heart has stopped start cardiopulmonary resuscitation (CPR) SIGNS AND SYMPTOMS OF OVEREXPOSURE:

No further relevant information available.

SECTION V – FIRE FIGHTING MEASUREHTING MEASURES

General Hazard: Thermal decomposition can lead to release of irritating gases and vapors Suitable Extinguishing Media: Alcolhol resistant foam, water spray, CO2, dry powder Unsuitable Extinguishing Media: Water jet.

Special Remarks and Advice for Firefighters: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

SECTION VI - ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb with non-combustible liquid binding material(sand, diatomaceous earth (clay), acid binders, universal binders.

LARGE SPILL: Wear appropriate personal protective equipment. Contain spill and pump into suitable disposal

ENVIRONMENTAL PRECAUTIONS:

WATER SPILL: Do not allow to enter drains or waterways. LAND SPILL: Should not be released into the environment.

GENERAL PROCEDURES: Ensure adequate ventilation. Ensure air handling systems are operational. All cleanup materials should be removed and placed in appropriate containers, labeled and stored in a a safe place prior to proper treatment or disposal

SECTION VII - HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid releases to the environment.

Handling: Use with adequate ventilation. Use personal protective equipment. Storage: Store in a well-ventilated area. mage. Store in original container. Storage Temperature: Normal temperature and conditions of warehousing.

SECTION VIII - EXPOSURE CONTROL MEASURES

Engineering Controls: Personal Protective Equipment:







SKIN: Protective Gloves

EYE: Wear chemical splash goggles and face shield

RESPIRATORY: A NIOSH/MSHA approved air supplied respirator is advised in absence of environmental control.

PROTECTIVE CLOTHING: Permeation resistant clothing and foot protection

WORK HYGIENIC PRACTICES: Employees should wash their hands and face before eating, drinking or using tobacco products.

OTHER PRECAUTIONS: Properly maintain a safety shower and eyewash facility in the work area



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Fluid **Physical State:** Color: Yellowish Odor: Ammonia -like pH-value: >No data available Boiling Point/Boiling Range: >200°C (392°F) Freezing Point: No data available Flash Point And Method: >100°C (212°F) Flammable Limits 1.3% to 13%

Auto Igniting: Product is not self-igniting.

Vapor Pressure:

Vapor Density:

Viscosity:

Solubility in water:

Evaporation Rate:

Flammability:

Thermal Decomposition:

No data available

No data available

No data available

Non-Flammable

No data available

SECTION X - REACTIVITY DATA

Conditions to be avoided: None known

Incompatible materials: Strong oxidizers, Alkalis, Peroxides and other radical forming substances Hazardous Decomposition Products: Combustion may produce oxides of carbon and nitrogen.

Reactivity: Stable under recommended storage conditions. Stability: Stable under normal conditions of use and storage.

Possibility of Hazardous Reactions: None known. Hazard Polymerization: None under normal processing

SECTION XI – TOXICOLOGICAL INFORMATION

Acute toxicity: Oral: Benzyl Alcohol: LD50 - Rat 1230 mg.kg

Likely Route of Exposure: Skin. Exposure Symptoms:

Eyes: Severe irritation, burns and blindness.

Skin: Harmful, causes skin burns.

Inhalation: Harmful. May cause delayed lung injury.

Ingestion: Severe mouth, throat, stomach and esophagus burns.

Effects (Short-term, Long-term):

Immediate: Skin and eye contact.

Delayed: Ingestion.

Chronic: NE

Carcinogenicity: No.

Sensitization: May cause skin sensitization.



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

SECTION XII - ECOLOGICAL INFORMATION

Aquatic toxicity:Cyclohexanemeth anamine, 5-amino-1,3,3-trimethyl- Aquatic invertebrates, LC50-Daphnia magna (water flea) 17.4 mg/L

Persistence and Degradability: No further relevant information available.

Behavior in Environmental Systems: No further relevant information available.

Bioaccumulative Potential: No further relevant information available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Recommendation: Dispose of according to local, state and federal regulations.

Additional Information: Refer to Section 8

SECTION XIV – TRANSPORT INFORMATION

UN-Number: 2735

UN Proper Shipping Name: Amines, Liquid, Corrosive, N.O.S.* (Isophorone Diamine)

Transport Hazard Class: 8
Packing Group: II





Limited Quantity: 5L

SECTION XV - OTHER REGULATORY INFORMATION

NFPA Ratings (Scale 0-4)





SECTION XVI - OTHER INFORMATION

Last Updated: 6/1/2019

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products. End of SDS.